

IONEX: The IONosphere Map EXchange Format Version 1.1

Stefan Schaer, Werner Gurtner
Astronomical Institute, University of Berne, Switzerland
stefan.schaer@aiub.unibe.ch

Joachim Feltens
ESA/ESOC, Darmstadt, Germany

February 25, 1998
September 17, 2015 (Update to V1.1)

Revision History

Update from V1.0 to V1.1:

- *Appendix B on Auxiliary Data Blocks* was completely removed. The exchange of GNSS differential code bias (DCB) values is no longer supported by IONEX (V1.1). The Bias-SINEX Format Version 1.00 shall be used for this purpose. Note that the records “START OF AUX DATA” and “END OF AUX DATA” are still included.
- “IONEX VERSION / TYPE”: Satellite system codes GPS and GLONASS are no longer available. GNSS (GNSS) must be used instead (GNSS was attributed to GPS/GLONASS in V1.0).
- “SYS / #STA / #SAT” record was introduced in order to allow proper declaration of all contributing GNSS. Although treated as optional, this record should be considered in case of (multi-)GNSS IONEX results.

Introduction

The International GPS Service for Geodynamics (IGS) provides precise GPS orbits, earth orientation parameters (EOPs), station coordinates, satellite clock information, and—on a test basis—tropospheric zenith delays. The IGS community is well aware of

Proceedings of the IGS AC Workshop, Darmstadt, Germany, February 9–11, 1998

the fact that the IGS network can also be used to extract information about the total electron content (TEC) of the ionosphere on a global scale. One may expect that the IGS will include TEC maps into its product palette in the near future.

As part of the 1996 IGS Workshop in Silver Spring, a first effort has been made to compare GPS-derived TEC maps produced by IGS Analysis Centers (CODE and ESA/E-SOC) as well as external processing centers (DLR Neustrelitz and University of New Brunswick) [Feltens, 1996a]. For this purpose, a very simple data exchange format proposed by Wilson (JPL) has been used.

One essential conclusion of the ionosphere-related discussion was that a common data format to exchange, compare, or combine TEC maps has to be defined. Based on a first format proposal by [Schaer, 1996], which strongly follows the Receiver INdependent EXchange format (RINEX) [Gurtner and Mader, 1990], [Schaer and Gurtner, 1996], and [Feltens, 1996b], we present a revised version of the so-called IONosphere map EXchange format (IONEX) that supports the exchange of 2- and 3-dimensional TEC maps given in a geographic grid.

The most important modifications with respect to [Schaer and Gurtner, 1996] are:

- Ionosphere maps given in an earth-fixed reference frame are supported only.
- Ionosphere maps are epoch-specific, i. e., they have to be interpreted as “snapshots” at certain epochs. Guidelines how to use IONEX TEC maps are formulated in the next section.
- In addition to TEC and RMS error maps, single-layer height maps are allowed, too.
- The option of 3-dimensional TEC maps has been included into IONEX, i. e., multi-layer models may be handled very easily by performing an additional loop over an equidistant height grid.
- TEC values are written using format `mI5` instead of `m(X1,I4)`. The definition of an exponent (see “EXPONENT”) should help to cover the necessary dynamic range of electron density.
- Further satellite systems and techniques have been added to the list (see “IONEX VERSION / TYPE”).
- A general escape sequence has been defined to include technique-related auxiliary data blocks in the header part of IONEX files.

Application of IONEX TEC Maps

We may use three different procedures to compute the TEC E as a function of *geocentric* latitude β , longitude λ , and universal time t , when we have the TEC maps $E_i = E(T_i), i = 1, 2, \dots, n$ at our disposal:

- Simply take the nearest TEC map $E_i = E(T_i)$ at epoch T_i :

$$E(\beta, \lambda, t) = E_i(\beta, \lambda), \quad (1)$$

where $|t - T_i| = \min$.

- Interpolate between consecutive TEC maps $E_i = E(T_i)$ and $E_{i+1} = E(T_{i+1})$:

$$E(\beta, \lambda, t) = \frac{T_{i+1} - t}{T_{i+1} - T_i} E_i(\beta, \lambda) + \frac{t - T_i}{T_{i+1} - T_i} E_{i+1}(\beta, \lambda), \quad (2)$$

where $T_i \leq t < T_{i+1}$.

- Interpolate between consecutive *rotated* TEC maps:

$$E(\beta, \lambda, t) = \frac{T_{i+1} - t}{T_{i+1} - T_i} E_i(\beta, \lambda'_i) + \frac{t - T_i}{T_{i+1} - T_i} E_{i+1}(\beta, \lambda'_{i+1}), \quad (3)$$

where $T_i \leq t < T_{i+1}$ and $\lambda'_i = \lambda + (t - T_i)$. The TEC maps are rotated by $t - T_i$ around the Z-axis in order to compensate to a great extent the strong correlation between the ionosphere and the Sun's position. Note that method (1) can be refined accordingly by taking the nearest *rotated* map: $E(\beta, \lambda, t) = E_i(\beta, \lambda')$.

From method (1) to method (3), one may expect an improvement of the interpolation results, therefore we recommend to use the last approach (3).

Grid interpolation algorithms to be used are not discussed in detail here. However, a simple 4-point formula should be adequate, if the IONEX grid is dense enough:

$$E(\lambda_0 + p \Delta\lambda, \beta_0 + q \Delta\beta) = (1 - p)(1 - q) E_{0,0} + p(1 - q) E_{1,0} + q(1 - p) E_{0,1} + pq E_{1,1},$$

where $0 \leq p < 1$ and $0 \leq q < 1$. $\Delta\lambda$ and $\Delta\beta$ denote the grid widths in longitude and latitude.




Figure 1: Bivariate interpolation using the nearest 4 TEC values $E_{i,j}$

General Format Description

Each IONEX file consists of a header section and a data section. The header section contains global information for the entire file and is placed at the beginning of the file. The header section contains header labels in columns 61–80 for each line contained in the header section. These labels are mandatory and must appear exactly as given in the IONEX descriptions. Note that the maximum record length is 80 bytes per record.

As record descriptors in columns 61–80 are mandatory, the programs reading an IONEX file should be able to decode the header records with formats according to the record descriptor, provided the records have been first read into an internal buffer.

We propose to allow free ordering of the header records, with the following exception:

- The “IONEX VERSION / TYPE” record must be the first record in a file.

There are further rules to be considered:

- Each value remains valid until changed by an additional header record!
- Fields of lines with formatted numbers must contain at least a “0” to facilitate reading with C language routines, i. e., empty fields are not permitted here.
- In principle there should be no blank lines. We recommend however to anticipate blank line skipping by the reading routines.

Writing and reading IONEX files one has to perform loops over up to a maximum of five arguments, namely: time (EPOCH), latitude (LAT), longitude (LON), height (HGT), and map type. Possible loops are:

- (a) map type, EPOCH, HGT, LAT, LON,
- (b) EPOCH, map type, HGT, LAT, LON.

Both enclosed examples have been created according to loop (a).

The proposed format descriptions as well as examples are given in the tables at the end of this paper.

Exchange of IONEX Files

We recommend to use the following naming convention for IONEX files:

cccedddh.yyI,

where

ccc: 3-figure Analysis Center (AC) designator
 e: extension or region code (“G” for Global ionosphere maps)
 ddd: day of the year of first record
 h: file sequence number (1, 2, . . .) or hour (A, B, . . .) within day;
 0: file contains all existing data of the current day
 yy: 2-digit year
 I: file type (“I” for Ionosphere maps).

Example: C0DG2880.95I. It is recommended to specify IONEX file names in uppercase.

When data transmission time or storage volume are critical we recommend to compress the files prior to storage or transmission using the UNIX compress und decompress programs. Compatible routines are available for VAX/VMS and PC/DOS systems.

Proposed naming conventions for compressed files:

System	Ionosphere files
UNIX	ccccdddh.yyI.Z
VMS	ccccdddh.yyI_Z
DOS	ccccdddh.yyJ

References

- Feltens, J. (1996a): *Ionosphere Maps—A New Product of IGS?* Summary of the Ionosphere Session, IGS Workshop, Silver Spring, MD, USA, March 19–21, 1996.
- Feltens, J. (1996b): *IONEX Format*. GPS-IONO mail, October 30, 1996.
- Gurtner, W., G. Mader (1990): *Receiver Independent Exchange Format Version 2*. CSTG GPS Bulletin, Vol. 3, No. 3, September/October 1990, National Geodetic Survey, Rockville.
- Schaer, S. (1996): *Proposal Concerning VTEC Data Format*. GPS-IONO mail, February 6, 1996.
- Schaer, S., W. Gurtner (1996): *IONEX: The IONosphere Map EXchange Format Version 0 (Proposal, August 1996)*. GPS-IONO mail, September 3, 1996.

Appendix A: IONEX Version 1.1 Format Definitions and Examples

Table 1: Ionosphere map file—header section description

HEADER LABEL (Columns 61-80)	DESCRIPTION	FORMAT
IONEX VERSION / TYPE	<ul style="list-style-type: none"> o Format version (1.1) o File type ('I' for Ionosphere maps) o Satellite system or theoretical model: <ul style="list-style-type: none"> - 'BEN': BENT - 'ENV': ENVisat - 'ERS': ERS - 'GEO': GEOstationary satellite(s) - 'GNS': GNSs - 'IRI': IRI - 'MIX': MIXed/combined - 'NNS': NNSs (transit) - 'TOP': TOPex/poseidon <p>This record has to be the first one in an IONEX file!</p>	F8.1,12X, A1,19X, A3,17X
PGM / RUN BY / DATE	<ul style="list-style-type: none"> o Name of program creating current file o Name of agency creating current file o Date and time of file creation 	A20, A20, A20
* DESCRIPTION	It is highly recommended to give a brief description of the technique, model, ... Please distinguish between description and pure comment.	A60
* COMMENT	Comment line(s). Note that comment lines are not allowed right at the beginning of a file or within TEC/RMS/HGT data blocks (see 'LAT/LON1/LON2/DLON/H').	A60
EPOCH OF FIRST MAP	Epoch of first TEC map (UT): year (4 digits), month, day, hour, min, sec (integer)	6I6,24X
EPOCH OF LAST MAP	Epoch of last TEC map (UT): year (4 digits), month, day, hour, min, sec (integer)	6I6,24X
INTERVAL	Time interval between the TEC maps, in seconds (integer). If '0' is specified, 'INTERVAL' may be variable.	I6,54X
# OF MAPS IN FILE	Total number of TEC/RMS/HGT maps contained in current file.	I6,54X
MAPPING FUNCTION	Mapping function adopted for TEC determination: 'NONE': no MF used (e.g. altimetry), 'COSZ': 1/cos(z), 'QFAC': Q-factor. Others might be introduced.	2X,A4,54X
ELEVATION CUTOFF	Minimum elevation angle in degrees. '0.0', if unknown; '90.0' for altimetry.	F8.1,52X
OBSERVABLES USED	One-line specification of the observable(s) used in the TEC computation (or blank line for theoretical models).	A60
* # OF STATIONS	Number of contributing stations.	I6,54X
* # OF SATELLITES	Number of contributing satellites.	I6,54X

* SYS / #STA / #SAT	o Each individual GNSS (system code) o # of stations o # of satellites Satellite system codes (from RINEX): 'G': GPS 'R': GLONASS 'E': Galileo 'J': QZSS 'C': BeiDou 'I': IRNSS 'S': SBAS payloads Note: SYS is mandatory in case of GNSS; #STA, #SAT might be blank/undefined.	5X,A1, I6, I6,42X	*
BASE RADIUS	Mean earth radius or bottom of height grid (in km), e.g.: 6371 km or 6771 km.	F8.1,52X	
MAP DIMENSION	Dimension of TEC/RMS maps: 2 or 3. See also 'TEC VALUES'.	I6,54X	
HGT1 / HGT2 / DHGT	Definition of an equidistant grid in height: 'HGT1' to 'HGT2' with increment 'DHGT' (in km), e.g.: ' 200.0 800.0 50.0'. For 2-dimensional maps, HGT1=HGT2 and DHGT=0, e.g.: ' 400.0 400.0 0.0' or ' 0.0 0.0 0.0' (see also 'BASE RADIUS').	2X,3F6.1, 40X	
LAT1 / LAT2 / DLAT	Definition of the grid in latitude: 'LAT1' to 'LAT2' with increment 'DLAT' (in degrees). 'LAT1' and 'LAT2' always have to be multiples of 'DLAT'. Example: ' 87.5 -87.5 -2.5'.	2X,3F6.1. 40X	
LON1 / LON2 / DLON	Definition of the grid in longitude: 'LON1' to 'LON2' with increment 'DLON' (in degrees), where LON equals east longitude. 'LON1' and 'LON2' always have to be multiples of 'DLON'. Example: ' 0.0 357.5 2.5' or ' -180.0 177.5 2.5'.	2X,3F6.1, 40X	
* EXPONENT	Exponent defining the unit of the values listed in the following data block(s). Default exponent is -1. See also 'TEC VALUES', 'RMS VALUES', and 'HGT VALUES'.	I6,54X	*
* START OF AUX DATA	Record opening general escape sequence that contains technique-related auxiliary data. Note that such data blocks may be skipped if you are interested in ionospheric information only.	A60	*
* END OF AUX DATA	Record closing auxiliary data block.	A60	*
END OF HEADER	Last record of the header section.	60X	
START OF TEC MAP	Record indicating the start of the i-th TEC map, where i=1,2,...,n denotes the internal number of the current map. All maps have to be ordered chronologically.	I6,54X	
EPOCH OF CURRENT MAP	Epoch of current map (UT): year (4 digits), month, day, hour, min, sec (integer). 'EPOCH OF CURRENT MAP' must be specified at the first occurrence of the associated map!	6I6,24X	

LAT/LON1/LON2/DLON/H	Record initializing a new TEC/RMS/HGT data block for latitude 'LAT' (and height 'H(GT)'), from 'LON1' to 'LON2' (with increment 'DLON'). In case of 2-dimensional maps, it is recommended to define H=HGT1. Neither other types of records nor comment lines are allowed after this record and within the subsequent data block!	2X,5F6.1, 28X	
END OF TEC MAP	Record indicating the end of the i-th TEC map (see also 'START OF TEC MAP').	I6,54X	
* START OF RMS MAP	Record indicating the start of an RMS map related to the i-th TEC map (see also 'START OF TEC MAP').	I6,54X	*
* END OF RMS MAP	Record indicating the end of an RMS map.	I6,54X	*
* START OF HEIGHT MAP	Record indicating the start of a HEIGHT map related to the i-th TEC map (see also 'START OF TEC MAP').	I6,54X	*
* END OF HEIGHT MAP	Record indicating the end of a HGT map.	I6,54X	*
END OF FILE	Last record closing the IONEX file.	60X	

(Records marked with “*” are optional)

Table 2: Ionosphere map file—data record description

OBS. RECORD	DESCRIPTION	FORMAT	
TEC VALUES	TEC values in 0.1 TECU. After 16 values (per latitude band) continue values in next data record. Non-available TEC values are written as '9999'. If an exponent k is specified, the TEC values are given in units of 10**k TECU. The default exponent is -1. See also 'EXPONENT'. If 3-dimensional maps are provided, TEC values should correspond to the surface electron densities at the grid points times 'DHGT' (again in 10**k TECU), that means, you can derive the surface electron densities by simply dividing the TEC values by 'DHGT'. However, if you estimate electron densities integrated over voxels (volume elements), you should ensure that the height grid specified in 'HGT1 / HGT2 / DHGT' refers to the heights of the voxel centers.	mI5	
* RMS VALUES	RMS values are formatted exactly in the same way as TEC values (see above).	mI5	*
* HGT VALUES	HGT values are formatted exactly in the same way as TEC values (see above). If an exponent k is specified, the HGT values are given in units of 10**k km. The default exponent is -1, too, i.e. in this case the unit corresponds to 0.1 km. The actual heights (with respect to the 'BASE RADIUS') are computed as the sum of 'HGT1' and 'HGT VALUES'.	mI5	*

(Records marked with “*” are optional)

Table 3: Ionosphere map file—example 1: 2-d TEC maps

```

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|
1.1 IONOSPHERE MAPS GNSS IONEX VERSION / TYPE
ionpgm v1.0 aiub 29-jan-96 17:29 PGM / RUN BY / DATE
example of an ionex file containing 2-dimensional tec maps COMMENT
global ionosphere maps for day 288, 1995 DESCRIPTION
modeled by spherical harmonics ... DESCRIPTION
1995 10 15 0 0 0 EPOCH OF FIRST MAP
1995 10 16 0 0 0 EPOCH OF LAST MAP
21600 INTERVAL
5 # OF MAPS IN FILE
COSZ MAPPING FUNCTION
20.0 ELEVATION CUTOFF
double-difference carrier phase OBSERVABLES USED
80 # OF STATIONS
24 # OF SATELLITES
G 80 24 SYS / #STA / #SAT
6371.0 BASE RADIUS
2 MAP DIMENSION
400.0 400.0 0.0 HGT1 / HGT2 / DHGT
85.0 -85.0 -5.0 LAT1 / LAT2 / DLAT
0.0 355.0 5.0 LON1 / LON2 / DLON
-1 EXPONENT
tec values in 0.1 tec units; 9999, if no value available COMMENT
height values in 0.1 km COMMENT
END OF HEADER
1 START OF TEC MAP
1995 10 15 0 0 0 EPOCH OF CURRENT MAP
85.0 0.0 355.0 5.0 400.0 LAT/LON1/LON2/DLON/H
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
80.0 0.0 355.0 5.0 400.0 LAT/LON1/LON2/DLON/H
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
... -85.0 0.0 355.0 5.0 400.0 LAT/LON1/LON2/DLON/H
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1 END OF TEC MAP
2 START OF TEC MAP
1995 10 15 6 0 0 EPOCH OF CURRENT MAP
85.0 0.0 355.0 5.0 400.0 LAT/LON1/LON2/DLON/H
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
... 5 END OF TEC MAP
1 START OF RMS MAP
85.0 0.0 355.0 5.0 400.0 LAT/LON1/LON2/DLON/H
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
80.0 0.0 355.0 5.0 400.0 LAT/LON1/LON2/DLON/H
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
...

```

```

-85.0 0.0 355.0 5.0 400.0 LAT/LON1/LON2/DLON/H
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1
END OF RMS MAP
2
START OF RMS MAP
85.0 0.0 355.0 5.0 400.0 LAT/LON1/LON2/DLON/H
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
...
5
END OF RMS MAP
1
START OF HEIGHT MAP
85.0 0.0 355.0 5.0 400.0 LAT/LON1/LON2/DLON/H
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
80.0 0.0 355.0 5.0 400.0 LAT/LON1/LON2/DLON/H
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
...
-85.0 0.0 355.0 5.0 400.0 LAT/LON1/LON2/DLON/H
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
1
END OF HEIGHT MAP
2
START OF HEIGHT MAP
85.0 0.0 355.0 5.0 400.0 LAT/LON1/LON2/DLON/H
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
...
5
END OF HEIGHT MAP
END OF FILE

```

```

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

```

Table 4: Ionosphere map file—example 2: 3-d TEC maps

```

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|
1.1 IONOSPHERE MAPS GNSS IONEX VERSION / TYPE
ionpgm v1.0 aiub 29-jan-96 17:29 PGM / RUN BY / DATE
example of an ionex file containing 3-dimensional tec maps COMMENT
global ionosphere maps for day 288, 1995 DESCRIPTION
modeled by spherical harmonics ... DESCRIPTION
1995 10 15 0 0 0 EPOCH OF FIRST MAP
1995 10 16 0 0 0 EPOCH OF LAST MAP
21600 INTERVAL
5 # OF MAPS IN FILE
COSZ MAPPING FUNCTION
20.0 ELEVATION CUTOFF
double-difference carrier phase OBSERVABLES USED
80 # OF STATIONS
24 # OF SATELLITES
G 80 24 SYS / #STA / #SAT
6371.0 BASE RADIUS
3 MAP DIMENSION
200.0 800.0 50.0 HGT1 / HGT2 / DHGT
85.0 -85.0 -5.0 LAT1 / LAT2 / DLAT

```



```

1000 1000 1000 1000 1000 1000 1000 1000
...
5                               END OF TEC MAP
1                               START OF RMS MAP
-3                              EXPONENT
85.0   0.0 355.0   5.0 200.0   LAT/LON1/LON2/DLON/H
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000 1000
1000 1000 1000 1000 1000 1000 1000 1000
...
5                               END OF RMS MAP
                                END OF FILE

----|---1|0---|---2|0---|---3|0---|---4|0---|---5|0---|---6|0---|---7|0---|---8|

```